

BLANK PAGE



Indian Standard SPECIFICATION FOR CABLE LIFTERS FOR WINDLASSES

UDC 621-864-078: 629-12-013



© Copyright 1973

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 1

March 1973

Indian Standard SPECIFICATION FOR CABLE LIFTERS FOR WINDLASSES

Marine Engineering Sectional Committee, MCPD 3

Chairman

SHRI B. K. GUPTA

Representing

Ministry of Parliamentary Affairs, Shipping and Transport

Members

SHRI R. C. MOHAN (Alternate to

Shri B. K. Gupta)

SHRI K. K. BANERJEE

Hindustan Shipyard Ltd, Visakhapatnam

SHRI C. M. RAO (Alternate)

SHRI A. S. BONDALE

Garden Reach Workshops Ltd. Calcutta Inter Ports Consultation Secretariat Cell. Calcutta

CHIEF MECHANICAL ENGINEER. CALCUTTA PORT COMMISSIONERS

CHIEF MECHANICAL ENGINEER.

BOMBAY PORT TRUST (Alternate)

AFCO Ltd, Bombay

SHRI V. G. DAMLE SHRI R. D. PARALKAR (Alternate)

DIRECTOR OF MARINE ENGINEERING Ministry of Defence (NHQ)

DEPUTY DIRECTOR OF MARINE

Engineering (Designs) (Alternate) SHRI H. M. GHATAK

Cummins Diesel Sales and Service (I) Pvt Ltd. Calcutta

SHRI F. D. GOMES

SHRI G. M. RANA (Alternate)

SHRI B. HILL

Lloyd's Register of Shipping, Calcutta

Scindia Workshop Ltd. Bombay

SHRI KIRPAL SINGH .

The Indian National Shipowners' Association, Bombay

Voltas Ltd. Bombav

SHRI V. T. KIRPLANI

SHRI S. V. DONGRAY (Alternate)

SHRI S. MAJUMDAR

SHRI K. N. G. MENON
SHRI K. A. IRANI (Alternate)

SHRI R. G. PHATAK SHRI M. A. NOORUDDIN

SHRI S. K. SAKSENA (Alternate)

SHRI T. S. RAJAN

*SHRI ANIAN ROYE

Directorate General of Technical Development The Shipping Corporation of India Ltd. Bombay

Kirloskar Oil Engines Ltd, Poona Siemens India Ltd. Bombay

Ericson & Richards, Bombay

Institution of Marine Technologists, Bombay

SHRI E. R. DASTOOR (Alternate) SHRI K. N. G. MENON (Alternate)

*Shri Anjan Rove is also alternate to Shri H. M. Ghatak representing Cummins Diesel Sales and Service (I) Pvt Ltd, Calcutta.

(Continued on page 2)

© Copyright 1973

INDIAN STANDARDS INSTITUTION

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS: 6675 - 1972

(Continued from page 1)

Members

Representing

SHRI T. M. SANGHAVI

SHRI L. NORBEDO (Alternate)

SHRI S. G. SCHAEFFER

SHRI K. SHARMA (Alternate)

SHRI SHIV NARAIN

Shri Harish Bhargava (Alternate)

Shri B. S. Sood

SHRI T. S. RAJAN (Alternate)

SHRI K. E. VARGHESE SHRI P. VASANTHA KUMAR (Alternate)

SHRI B. D. WADIA SHRI I. J. VARMA (Alternate)

SHRI K. S. SUBRAMANIAM, Duty Officer on Special

(MCPD) (Secretary)

Bureau Veritas, Meecon Pvt Ltd, Bombay

American Bureau of Shipping, Bombay

Escorts Ltd, Bombay

The Institute of Marine Engineers, Bombay

Cochin Shipyard Project, Cochin

Jayanti Shipping Co Ltd, Bombay

Director General, ISI (Ex-officio Member)

Winches, Windlasses and Steering Gears Subcommittee, MCPD 3:4

Convener

SHRI F. D. GOMES

Members

SHRI G. M. RANA (Alternate to

Shri F. D. Gomes)

SHRI V. G. DAMLE

SHRI R. D. PARALKAR (Alternate)

Shri J. E. D'Souza Shri B. Hill

SHRI S. RATRA (Alternate)

Shri J. M. Khanna

SHRI S. S. KAKKAR (Alternate) SHRI I. C. NANGIA

SHRI J. K. NANGIA (Alternate) SHRI M. A. NOORUDDIN

SHRI S. K. SAKSENA (Alternate)

SHRI R. RAMACHANDRAN

Shri K. Ramakrishnan

SHRI V. B. VERMA (Alternate)

SHRI M. G. RANE

SHRI S. SATYANARAYANA SHRI B. SAHEB NAIDU (Alternate)

SHRI S. G. SCHAEFFER

SHRI K. SHARMA (Alternate)

SHRI P. A. SHAPARIA

SHRI C. N. MISTRY (Alternate)

... TION DESIGNS.)

Scindia Workshop Ltd, Bombay

AFCO Ltd, Bombay

The Shalimar Works Ltd, Calcutta Lloyd's Register of Shipping, Calcutta

Usha Telehoist Ltd, Calcutta

Geeta Engineering Works (Pvt) Ltd. Bombay

Siemens India Ltd, Bombay

Inter Port Consultation Secretariat Cell, Calcutta Ministry of Parliamentary Affairs, Shipping and Transport

Bharati Engineering Co, Bombay

Hindustan Shipyard Ltd, Visakhapatnam

American Bureau of Shipping, Bombay

Shaparia Dock & Steel Co Pvt Ltd, Bombay

STAFF OFFICER (NAVAL CONSTRUC- Ministry of Defence (NHQ)

Indian Standard SPECIFICATION FOR CABLE LIFTERS FOR WINDLASSES

0. FOREWORD

- 0.1 This Indian Standard was adopted by the Indian Standards Institution on 18 October 1972, after the draft finalized by the Marine Engineering Sectional Committee had been approved by the Marine, Cargo Movement and Packaging Division Council.
- 0.2 Windlass is one of the compulsory deck equipment which has to be fitted on board ships for dropping and heaving of anchors by means of chain cables. Cable lifter is the wheel mounted on the windlass shaft provided with five snugs. When the anchor is dropped or heaved, the anchor chain links pass over the snugs on the wheel without fouling.
- 0.3 In the preparation of this standard, assistance has been derived from UNAV 6044 'Cable lifter with five snugs', issued by Ente Nazionale Italiano di Unificazione.
- 0.4 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard specifies the material and dimensions for cable lifters fitted to windlasses.

2. TERMINOLOGY

- 2.0 For the purpose of this standard, the following definitions shall apply.
- 2.1 Cable Lifter Cable lifter is a special wheel with sprockets fitted on to the windlass shaft, to wind and unwind studlink or studless link chains, with kenter or 'Dee' shackles, while dropping or heaving the anchor. A cable lifter is also known as gypsy wheel, messenger wheel, cable holder or wild cat.

^{*}Rules for rounding off numerical values (revised).

IS: 6675 - 1972

- 2.2 Nominal Size The nominal size of the cable lifter is the diameter of the common link of the anchor chain. One cable lifter may be used for two or more diameters of anchor chain link and in such cases, the nominal size is indicated with respect to the largest diameter of common link of the anchor chain in that group.
- 2.3 Snugs These are the sprockets on the cable lifter for taking the horizontal links of chain cable for positively driving it when the windlass is operated. Five snugs are generally used with each cable lifter, with the heaving angle of the anchor chain not less than 110° (see Fig. 1).




Fig. 1 Cable Lifter with Five Sprockets with Chain and Chain Pipe

3. CONSTRUCTION

- 3.1 The cable lifters shall be bushed to run free on their shafts to enable them run freely under the control of brakes, if required. Ploughs or chain strippers should be fitted to prevent the cables jamming.
- 3.2 Cable lifters shall be designed to withstand safely all service loads and also the stresses that may result at the commencement of the heaving operation.

4. MATERIAL

4.1 Cable lifters shall be made of cast iron or cast steel as indicated below:

Cast steel IS: 1030-1962* or Weldable

IS: 2985-1964† } quality

Cast iron IS: 210-1970‡ Grade 20 or above

5. DIMENSIONS

5.1 The dimensions of cable lifters for various nominal sizes shall be in accordance with Table 1. The dimensions are worked out for taking chain cables conforming to IS: 4484-1967§ and IS: 4692-1968||.

5.2 The dimension D_1 is given by:

$$D_1 = \frac{2 p}{\sin \frac{180}{n}}$$

where

 $D_1 = \text{pitch circle diameter (see Fig. 1)},$

p = pitch of chain (see Fig. 1), and

n = number of snugs.

6. TOLERANCE

6.1 The tolerance in millimetres on dimensions of cable lifters shall be ±2 percent.

7. DESIGNATION

7.1 Cable lifters shall be designated by the nominal size, and the number of this standard.

Example:

A cable lifter of nominal size 43 shall be designated as: Cable lifter 43 IS: 6675.

8. MARKING

8.1 Cable lifter shall be marked with designation on its side.

^{*}Specification for steel castings for general engineering purposes (revised).

[†]Specification for steel castings for ship's structure.


[†]Specification for grey iron castings (second revision).

[§]Specification for electrically welded stud link anchor chains and attachments.

Specification for electrically welded studless link anchor chains and attachments.

(Clause 5.1)

All dimensions in millimetres.



σ

| Nominal Size d | *a (4·5d + 10) | *b (4·3d + 10) | *c (1.5d +5) | $\begin{vmatrix} *D \\ (D_1 + \\ 3.8d) \end{vmatrix}$ | *D ₁ (13·6d) | *d ₁ (7·1d) | $\begin{pmatrix} *d_2 \\ (D_1+d) \end{pmatrix}$ | *d ₃ (10·7d) | *d ₄ (8·9d) | *R (6.5d) | *R ₁ (7.8d) | *R ₂ | *R ₃ | Nominal Size of Cable Lifter |
|----------------------------|---------------------------------|---------------------------------|------------------------------|-------------------------------------------------------|---------------------------------|---------------------------------|-------------------------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|----------------------------|----------------------------------|---------------------------------------|
| (1) | (2) | (3) | (4) | -(5) | (6) | (7) | (8) | (9) | (10) | (11) | (12) | (13) | (14) | (15) |
| 12·5 | 66 | 64 | 24 | 218 | 170 | 89 | 182 | 134 | 111 | 81 | 97 | 3 | 3 | 14 |
| 14 | 73 | 70 | 26 | 244 | 190 | 99 | 204 | 150 | 125 | 91 | .109 | 3 | | 14 |
| 16 | 82 | 79 | 29 | 278 | 218 | 114 | 234 | 171 | 142 | 104 | 125 | 3 3 | 3 | 17 |
| 17 | 86 | 83 | 31 | 296 | 231 | 121 | 248 | 182 | 151 | 110 | 133 | | 3 | 17 |
| 19 | 96 | 92 | 33 | 331 | 258 | 135 | 277 | 203 | 169 | 124 | 148 | 4 | 3 | 21 |
| 21 | 1 04 | 100 | 37 | 365 | 286 | 149 | 307 | 225 | 187 | 136 | 164 | 5 | | 21 |
| 23 | 114 | 109 | 40 | 400 | 313 | 163 | 358 | 246 | 205 | 150 | 179 | 5 | 4 | 25 |
| 2 5 | 122 | 118 | 43 | 435 | 340 | 178 | 365 | 268 | 222 | 156 | 195 | 6 | 5 | 25 |
| 27 | 132 | 126 | 46 | 470 | 367 | 192 | 394 | 289 | 240 | 176 | 211 | 6 | 5 | 31 |
| 29 | 140 | 135 | 49 | 505 | 394 | 206 | 423 | 310 | 258 | 188 | 226 | 7 | 6 | 31 |
| 31 | 150 | 143 | 52 | 539 | 422 | 220 | 45 3 | 332 | 276 | 202 | 242 | 7 | 6 | 31 |
| 33 35 37 40 43 | 158 168 176 190 204 | 152 160 169 182 195 | 55 58 61 66 70 | 574 609 644 696 748 | 449 476 503 544 585 | 234 248 263 284 305 | 482 511 540 584 628 | 353 374 396 428 460 | 294 312 329 356 383 | 214 228 240 260 280 | 257 273 289 312 335 | 7 8 8 9 | 6 6 7 7 8 | 43 43 43 43 43 |
| 46 | 217 | 208 | 74 | 800 | 626 | 327 | 672 | 492 | 409 | 299 | 359 | 11 | 9 | 53 |
| 48 | 226 | 216 | 77 | 835 | 653 | 341 | 701 | 514 | 427 | 312 | 374 | 11 | 9 | 53 |
| 50 | 235 | 225 | 80 | 870 | 680 | 355 | 730 | 535 | 445 | 325 | 390 | 12 | 9 | 53 |
| 53 | 248 | 238 | 85 | 922 | 721 | 376 | 774 | 567 | 472 | 344 | 413 | 12 | 10 | 5 3 |
| 56 58 61 63 66 | 262 271 284 294 307 | 251 259 272 281 294 | 89 92 96 100 104 | 974 1 009 1 061 1 096 1 148 | 762 789 830 857 898 | 398 412 433 447 469 | 818 847 891 920 964 | 599 621 653 674 706 | 498 516 543 561 587 | 364 377 396 410 429 | 437 452 476 491 515 | 13 13 14 14 14 | 10 10 11 11 11 12 | 66 66 66 66 |

^{*}The proportions indicated are approximate.

TABLE 1 CABLE LIFTER (GYPSY WHEEL) — Contd

| Nominal Size d | *a (4.5d + 10) | *b (4·3d + 10) | *c (1.5d +5) | $\begin{pmatrix} *D \\ (D_1 + \\ 3.8d) \end{pmatrix}$ | *D ₁ (13·6d) | *d ₁ (7:1d) | $\begin{pmatrix} *d_2 \\ (D_1 + d) \end{pmatrix}$ | $*d_3 \ (10.7d)$ | *d ₄ (8·9d) | *R (6.5d) | *R ₁ (7·8d) | *R2 | *R ₃ | Nominal Size of Cable Lifter |
|---------------------------------|---------------------------------|---------------------------------|---------------------------------|-------------------------------------------------------|-------------------------------------------|-----------------------------------|---------------------------------------------------|-------------------------------------------|-------------------------------------------|----------------------------------------------|---------------------------------------|----------------------------------|----------------------------|---------------------------------------|
| (1) | (2) | (3) | (4) | (5) | (6) | (7) | (8) | (9) | (10) | (11) | (12) | (13) | (14) | (15) |
| 68 71 73 76 78 | 316 330 338 352 361 | 302 315 324 337 345 | 107 112 114 119 122 | 1 183 1 235 1 270 1 322 1 357 | 925 966 993 1 034 1 061 | 483 504 518 540 554 | 993 1 037 1 066 1 110 1 139 | 728 760 781 813 835 | 605 632 650 676 694 | 442 ⁻ 462 474 494 507 | 530 554 570 593 608 | 15 16 16 16 16 | 13 13 13 13 13 | 78 78 78 78 78 78 |
| 81 83 85 87 92 | 374 384 392 402 424 | 358 367 376 384 406 | 126 130 133 136 143 | 1 409 1 444 1 479 1 514 1 601 | 1 102 1 129 1 156 1 183 1 251 | 575 589 604 618 653 | 1 183 1 212 1 241 1 270 1 343 | 867 888 910 931 984 | 721 739 756 774 819 | 526 540 552 566 598 | 632 647 663 679 718 | 17 17 17 17 17 | 14 14 14 14 14 | 92 92 92 92 92 |
| 97 102 107 112 117 | 446 469 492 514 536 | 427 449 470 492 513 | 150 158 166 173 180 | 1 688 1 775 1 862 1 949 2 036 | 1 319 1 387 1 455 1 523 1 591 | 689 724 760 795 831 | 1 416 1 489 1 562 1 635 1 708 | 1 038 1 091 1 145 1 198 1 252 | 863 908 952 997 1 041 | 630 663 696 728 760 | 757 796 835 874 913 | 18 18 18 19 19 | 15 15 15 16 16 | 117 117 117 117 117 |
| 122 127 132 137 142 | 559 582 604 626 649 | 535 556 578 599 621 | 188 196 203 210 218 | 2 123 2 210 2 297 2 384 2 471 | 1 659 1 727 1 795 1 863 1 931 | 866 902 937 973 1 008 | 1 781 1 854 1 927 2 000 2 073 | 1 305 1 359 1 412 1 466 1 519 | 1 086 1 130 1 175 1 219 1 264 | 793 826 858 890 923 | 952 991 1 030 1 069 1 108 | 19 20 20 20 20 21 | 16 17 17 17 17 | 142 142 142 142 142 |
| 147 152 | 672 694 | 642 664 | 226 233 | 2 558 2 645 | 1 999 2 067 | 1 043 1 079 | 2 146 2 219 | 1 57 3 1 6 2 6 | 1 308 1 3 53 | 956 988 | 1 147 1 186 | 21 21 | 18 18 | 152 1 52 |

^{*}The proportions indicated are approximate.

PUBLICATIONS OF INDIAN STANDARDS INSTITUTION

INDIAN STANDARDS

Over 7 000 Indian Standards covering various subjects have been issued so far. Of these, the standards belonging to the Marine, Cargo Movement and Packaging Group fall under the following categories:

MARINE

Br

Anchors and anchor cables
Diesel engines
Distress signals
Fire safety
Inland vessels
Life saving equipment & accessories
Magnetic compasses
Mooring equipment
Navigational lights
Piping systems, valves & accessories
Ship's derricks and accessories
Ship's side scuttles & windows
Ventilation
Miscellaneous

CARGO MOVEMENT

Cargo marking, handling and stowing Freight containers Industrial trucks, tractors and trailers Lifting chains, associated fittings and components Pallets

PACKAGING

Glass containers
Metal containers
Paper and flexible packaging
Plastics containers
Wood and wood products containers

OTHER PUBLICATIONS

| ISI Bulletin (Published Eve | ry Month | 1) | | | | | |
|------------------------------|----------|--------|-----|-----|-----|---------|-------|
| Single Copy | | | | | | Rs | 3-00 |
| Annual Subscription | | 0 0 | *** | | | Rs 2 | 25-00 |
| Standards: Monthly Additio | ns | | | | | | |
| Single Copy | *** | | | | *** | Re | 0-30 |
| Annual Subscription | | | | ••• | | Rs | 3.00 |
| Annual Reports (from 1948 | -49 Onwa | irds) | *** | | Rs | 2.00 to | 5-00 |
| ISI Handbook, 1972 | | | | ••• | | Rs 2 | 20-00 |

INDIAN STANDARDS INSTITUTION

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 1

Telephone: 27 01 31 (20 lines) Telegrams: Manaksanstha

| ranch Offices: | | Telephone |
|--------------------------------------------|-------------|-----------|
| ' Sadhna', Nurmohamed Shaikh Marg, Khanpur | Ahmedabad 1 | 2 03 91 |
| F Block, Unity Bldg, Narasimharaja Square | Bangalore 2 | 2 76 49 |
| 534 Sardar Vallabhbhai Patel Road | Bombay 7 | 23-08 02 |
| 5 Chowringhee Approach | Calcutta 13 | 35 69 44 |
| 5-9-201/2-A (First Floor), Chirag All Lane | Hyderabad 1 | 3 44 35 |
| 117/418 B Sarvodaya Nagar | Kanpur 5 | 82 72 |
| 54 General Patters Road | Madras | 8 72 78 |